

Tubes Roulés Soudés Ronds / Corrosion - Canalisation

NFEN 10217-7				1.4307 304L	1.4404 316L
Ø	ép.	~kg/ml	Pouces Schedules	Brossé ou décapé	
8,00	1,00	0,18		●	
10,0	1,00	0,23		●	●
12,0	1,00	0,28		●	●
13,7	1,65	0,50	1/4 - 10S	●	
13,7	2,24	0,64	1/4 - 40S	●	●
14,0	1,00	0,33		●	●
14,0	1,50	0,47		●	
16,0	1,00	0,38		●	
17,2	1,60	0,62		●	●
17,2	2,30	0,86	3/8 - 40S	●	●
21,3	1,60	0,79		●	●
21,3	2,00	0,97		●	●
21,3	2,11	1,01	1/2 - 10S	●	●
21,3	2,60	1,22		●	●
21,3	2,77	1,29	1/2 - 40S	●	●
23,0	1,50	0,81		●	
26,7	2,11	1,30	3/4 - 10S	●	●
26,7	2,87	1,71	3/4 - 40S		●
26,9	1,60	1,01		●	●
26,9	2,00	1,25		●	●
26,9	2,60	1,58		●	●
33,0	1,50	1,18		●	
33,4	2,77	2,12	1 - 10S	●	●
33,4	3,38	2,54	1 - 40S	●	●
33,7	1,60	1,29		●	●
33,7	2,00	1,59		●	●
33,7	2,60	2,02		●	●
33,7	3,20	2,44		●	●
42,4	1,60	1,63		●	●
42,4	2,00	2,02		●	
42,4	2,60	2,59		●	●
42,4	2,77	2,75	1 1/4 - 10S	●	●
42,4	3,20	3,14		●	●
42,4	3,56	3,46	1 1/4 - 40S	●	●
43,0	1,50	1,56		●	●
48,3	1,60	1,87		●	●
48,3	2,00	2,32		●	●

48,3	2,77	3,16	1 1/2 - 10S	●	●
48,3	3,20	3,61		●	●
48,3	3,68	4,11	1 1/2 - 40S	●	●
53,0	1,50	1,93		●	●
54,0	2,00	2,60		●	
60,3	1,60	2,35		●	●
60,3	2,00	2,92		●	●
60,3	2,77	3,99	2 - 10S	●	●
60,3	3,00	4,30		●	
60,3	3,60	5,11		●	●
60,3	3,91	5,52	2 - 40S	●	●
70,0	2,00	3,41		●	
73,0	1,50	2,69		●	●
73,0	3,05	5,34	2 1/2 - 10S	●	●
73,0	5,16	8,77	2 1/2 - 40S	●	●
76,1	1,60	2,98		●	●
76,1	2,00	3,71		●	●
76,1	3,00	5,49		●	●
76,1	3,60	6,54		●	●
76,1	5,16	8,77	2 1/2 - 40S		●
80,0	2,00	3,91		●	
83,0	1,50	3,06		●	
84,0	2,00	4,11		●	
88.9	1,60	3,50		●	
88.9	2,00	4,35		●	
88.9	3,00	6,45		●	
88.9	3,05	6,56	3 - 10S	●	
88.9	4,00	8,50		●	
88.9	5,49	11,47	3 - 40S	●	
101.6	3,05	7,53	3 1/2 - 10S	●	
101.6	2,00	4,99		●	
101.6	3,00	7,41		●	
103	1,50	3,81		●	
104	2,00	5,11		●	
114.3	1,60	4,52		●	
114.3	2,00	5,62		●	
114.3	3,00	8,36		●	
114.3	3,05	8,50	4 - 10S	●	
114.3	4,00	11,05		●	
114.3	6,02	16,32	4 - 40S		